

H0008 Pressure Settings and Flow rates for Sidelifters

H0008	Version 7	Hydraulics	13 Feb 07
-------	-----------	------------	-----------

Model Speed	Pressure (Mpa)	Flow l/m	Overcentre Valve settings MPa			Overcentre Valve Supplier
			Bottom arm (MPa) "A" side	Bottom arm (MPa) "B" side	Top arm (MPa) "A" side	

SE400

High	14	120	32.5	32.5	32.5	Integrated
Low	28	60				

SB361/401

High	14	120	32.5	32.5	32.5	Integrated
Low	28	60				

SB360

			34.5	34.5	34.5	Sun Cartridges
High	14	120	32.5	32.5	32.5	Integrated
Low	28	60				

SB300

High	14	120	32.5	34.5	32.5	Integrated
Low	28	60				

SB330

High	14	120	32.5	32.5	32.5	Integrated
Low	28	60				

SB180

High	14	60	32.5	32.5	32.5	Integrated
Low	28	13				

MK4R	28	37x2	34.5	34.5	34.5	Fluid Controls
MK4T	28	25x2	34.5	34.5	34.5	Fluid Controls

SB12	23.5	50	34.5	34.5	34.5	Fluid Controls
------	------	----	------	------	------	----------------

SB14	28	50	34.5	34.5	34.5	Fluid Controls
------	----	----	------	------	------	----------------

SB04	12	16 x 2	8.5 (can be set at 12.5)	12.5	10 (can be set at 12.5)	Integrated Fitted from 6904
------	----	--------	--------------------------	------	-------------------------	-----------------------------